

PLEASE AMEND THE CLAIMS AS INDICATED:

1. (currently amended) An inkjet printing apparatus which moves a media sheet along a media path and marks the media sheet with ink, comprising:

an inkjet printhead having a plurality of inkjet nozzles which eject ink onto a portion of the media sheet located within a print zone, the print zone located adjacent to the plurality of nozzles;

a support which supports the media sheet as the media sheet passes along the media path through the print zone;

a roller located upstream along the media path prior to the print zone, the roller stabilizing the media sheet relative to a first surface during printing onto at least a first portion of the media sheet;

a guide shim located along the media path, the guide shim having a guide surface extending at least from the roller, beyond the roller toward the print zone during printing, the guide shim acting upon a portion of the media sheet between the roller and the print zone to keep the media sheet out of contact with the printhead;

the guide shim capable of being advanced along the media path between a first position in which the guide shim is located upstream from the print zone along the media path and a second position in which at least a portion of the guide shim is located in the print zone; and

an advancing means operable to move for advancing the guide shim from the first position to the second position once the a trailing edge of the media sheet reaches a prescribed location along the media path, the guide shim being advanced with the media sheet.~~along the media path into the print zone during printing to at least a third portion of the media sheet.~~

2. (original) The apparatus of claim 1, in which the advancing means comprises means for advancing the guide shim into the print zone while a trailing edge of the media sheet moves into the print zone.

3. (original) The inkjet printing apparatus of claim 1, in which the roller is a first roller and further comprising a second roller located downstream along the media path after the print zone, the second roller stabilizing the media sheet relative

to a second surface during printing onto at least a second portion of the media sheet.

DS  
Ant

4. (currently amended) The inkjet printing apparatus of claim ~~6~~ 1, in which the support is an endless belt, and wherein the endless belt comprises an outer surface upon which the media sheet rests, the outer surface being said first surface ~~and said second surface~~.

5. (currently amended) The inkjet apparatus of claim ~~6~~ 3, in which the support moves along a path between the first roller and second roller while supporting a trailing portion of the media sheet.

6. (currently amended) The inkjet apparatus of claim 1, wherein the advancing means includes further comprising:

a sensor which detects position of the media sheet and generates in response a sensor signal; and

an actuator, means responsive to the sensor signal, and operable to for activating the advancing means to move the guide shim along the media path between the first position and the second position.

7. (original) The inkjet apparatus of claim 1, in which the inkjet printhead is a pagewide array printhead.

8. (original) The inkjet apparatus of claim 1, in which the inkjet printhead is a scanning type printhead which scans across the media sheet in a direction orthogonal to the direction of media sheet movement along the media path.

9. (original) The inkjet apparatus of claim 1, in which the plurality of inkjet nozzles are organized into a plurality of rows, each row extending in a direction orthogonal to the direction of media sheet movement along the media path.

10. (original) A method for advancing a media sheet along a media path through a print zone of an inkjet printing apparatus, the apparatus including an inkjet

printhead having a plurality of inkjet nozzles which eject ink, the print zone located adjacent to the plurality of nozzles, the method comprising the steps of:

receiving the media sheet at a roller which stabilizes the media sheet along the media path relative to a first surface, the roller located upstream along the media path prior to the print zone;

moving the media sheet under a guide shim toward the print zone, the guide shim acting upon a portion of the media sheet to maintain flatness and advance accuracy of the media sheet as a trailing edge of the media sheet travels beyond the roller toward the print zone;

ejecting ink onto a portion of the media sheet located within the print zone; and

advancing the guide shim along the media path into the print zone while a trailing portion of the media sheet moves into the print zone.

11. (original) The method of claim 10, in which the roller is a first roller and further comprising the step of receiving the media sheet at a second roller which stabilizes the media sheet along the media path relative to a second surface, the second roller located downstream along the media path after the print zone.

12. (original) The method of claim 11, in which the inkjet printing apparatus includes an endless belt which supports the media sheet as the media sheet passes along the media path through the print zone, wherein the step of receiving the media sheet at the first roller comprises pressing the media sheet to the endless belt, wherein the step of receiving the media sheet at the second roller comprises pressing the media sheet to the endless belt, the endless belt comprising the first surface and the second surface.

13. (original) The method of claim 11, in which the inkjet printing apparatus includes an endless belt which supports the media sheet as the media sheet passes along the media path through the print zone, and wherein the step of moving the media sheet under a guide shim toward the print zone comprises the step of driving the endless belt to carry the media sheet under the guide shim toward the print zone.

14. (original) The method of claim 10, further comprising the step of detecting a trailing edge of the media sheet, and in which the step of advancing comprises advancing the guide shim along the media path in response to the detection of the trailing edge.

RS  
ant

15. (original) The method of claim 10, further comprising the steps of:  
moving the media sheet onto a support; and  
moving the support along a path away from the roller while supporting a trailing portion of the media sheet during printing to at least a portion of the media sheet.

16. (original) The method of claim 15, in which the roller is a first roller and in which the step of moving the support comprises moving the support along a path between the first roller and a second roller while supporting a trailing portion of the media sheet during printing to at least a portion of the media sheet, the second roller located downstream along the media path after the print zone.

---